FLIGHT SUMMARY REPORT

Flight Number:	99-073
Calendar/Julian Date:	20 May 1999 • 140
Sensor Package:	Wild-Heerbrugg RC-10 Airborne Visible and Infrared Imaging Spectrometer (AVIRIS) Modis Airborne Simulator (MAS 50)
Area(s) Covered:	Rochester, NY

Investigator(s): Simmons, Eastman Kodak **Aircraft #:** 809

SENSOR DATA

Accession #:	05343	-----	-----
Sensor ID #:	034	099	108
Sensor Type:	RC-10	AVIRIS	MAS 50
Focal Length:	12” 304.66 mm	-----	-----
Film Type:	Aerochrome IR SO-134	-----	-----
Filtration:	Wratten 12	-----	-----
Spectral Band:	510-900 nm	-----	-----
f Stop:	11	-----	-----
Shutter Speed:	1/250	-----	-----
# of Frames:	20	-----	-----
% Overlap:	60	-----	-----
Quality:	Excellent	-----	-----
Remarks:	Subtract 94 seconds for correct UTC		

Airborne Science and Applications Program

The Airborne Science Branch at NASA's Dryden Flight Research Center, Edwards, California, operates two ER-2 high altitude aircraft in support of NASA earth science research. The ER-2s are used as readily deployable high altitude sensor platforms to collect remote sensing and in situ data on earth resources, celestial phenomena, atmospheric dynamics, and oceanic processes. Additionally, these aircraft are used for electronic sensor research and development and satellite investigative support.

The ER-2s are flown from various deployment sites in support of scientific research sponsored by NASA and other federal, state, university, and industry investigators. Data are collected from deployment sites in Kansas, Texas, Virginia, Florida, and Alaska. Cooperative international scientific projects have deployed the aircraft to sites in Great Britain, Australia, Chile, and Norway.

Photographic and digital imaging sensors are flown aboard the ER-2s in support of research objectives defined by the sponsoring investigators. High resolution mapping cameras and digital multispectral imaging sensors are utilized in a variety of configurations in the ER-2s' four pressurized experiment compartments. The following provides a description of the digital multispectral sensor(s) and camera(s) used for data collection during this flight.

Airborne Visible and Infrared Imaging Spectrometer

The Airborne Visible and Infrared Imaging Spectrometer (AVIRIS) is the second in the series of imaging spectrometer instruments developed at the Jet Propulsion Laboratory (JPL) for earth remote sensing. This instrument uses scanning optics and four spectrometers to image a 614 pixel swath simultaneously in 224 contiguous spectral bands (0.4-2.4 mm).

AVIRIS parameters are as follows:

IFOV:	1 mrad
Ground Resolution:	66 feet (20 meters) at 65,000 feet
Total Scan Angle:	30°
Swath Width:	5.7 nmi (10.6 km) at 65,000 feet
Spectral Coverage:	0.41-2.45 mm
Pixels/Scan Line:	614
Number of Spectral Bands:	224
Digitization:	10-bits
Data Rate:	17 MBPS

Spectrometer	Wavelength Range	Number of Bands	Sampling Interval
1	0.41 - 0.70 mm	31	9.4 nm
2	0.68 - 1.27 mm	63	9.4 nm
3	1.25 - 1.86 mm	63	9.7 nm
4	1.84 - 2.45 mm	63	9.7 nm

All AVIRIS data is decommutated and archived at JPL and not currently available for public distribution. For further information contact Rob Green at Jet Propulsion Laboratory, 4800 Oak Grove Drive, Mail Stop 183-501, Pasadena, California 91109-8099.

MODIS Airborne Simulator

The MODIS Airborne Simulator (MAS) is a modified Daedalus multispectral scanner configured to replicate the capabilities of the Moderate-Resolution Imaging Spectrometer (MODIS), an instrument to be orbited on an EOS platform. MODIS is designed for the measurement of biological and physical processes and atmospheric temperature sounding. The MODIS Airborne Simulator records fifty 16-bit channels of multispectral data and is configured as follows:

Spectral Channel	Band center (µm)	Bandwidth (µm)	Spectral Range
1	0.4649	0.0397	0.4451-0.4848
2	0.5494	0.0417	0.5285-0.5703
3	0.6550	0.0511	0.6294-0.6805
4	0.7024	0.0415	0.6816-0.7231
5	0.7431	0.0420	0.7221-0.7641
6	0.8248	0.0427	0.8034-0.8461
7	0.8667	0.0414	0.8460-0.8874
8	0.9072	0.0409	0.8867-0.9276
9	0.9476	0.0397	0.9277-0.9674
10	1.6422	0.0519	1.6163-1.6682
11	1.6975	0.0505	1.6722-1.7228
12	1.7499	0.0506	1.7245-1.7752
13	1.8014	0.0491	1.7768-1.8259
14	1.8548	0.0489	1.8303-1.8792
15	1.9044	0.0487	1.8801-1.9288
16	1.9553	0.0483	1.9312-1.9794
17	2.0048	0.0487	1.9804-2.0291
18	2.0551	0.0484	2.0309-2.0793
19	2.1037	0.0486	2.0794-2.1280
20	2.1532	0.0483	2.1291-2.1774
21	2.2019	0.0481	2.1779-2.2259
22	2.2522	0.0486	2.2278-2.2675
23	2.3021	0.0487	2.2777-2.3265
24	2.3512	0.0476	2.3274-2.3750
25	2.4005	0.0483	2.3764-2.4246

Spectral Channel	Band center (µm)	Bandwidth (µm)	Spectral Range
26	3.1192	0.1616	3.0384-3.2000
27	3.2809	0.1486	3.2066-3.3552
28	3.4330	0.1617	3.3521-3.5138
29	3.5940	0.1539	3.5170-3.6709
30	3.7449	0.1449	3.6724-3.8174
31	3.9069	0.1602	3.8267-3.9870
32	4.0707	0.1554	3.9929-4.1484
33	4.1699	0.0669	4.1365-4.2034
34	4.4029	0.1255	4.3401-4.4656
35	4.5404	0.1512	4.4648-4.6160
36	4.6979	0.1591	4.6184-4.7775
37	4.8536	0.1516	4.7778-4.9294
38	5.0033	0.1468	4.9298-5.0767
39	5.1588	0.1400	5.0888-5.2288
40	5.3075	0.1327	5.2412-5.3738
41	5.3977	0.0755	5.3590-5.4365
42	8.5366	0.3950	8.3391-8.7341
43	9.7224	0.5365	9.4541-9.9906
44	10.5071	0.4579	10.278-10.736
45	11.0119	0.4710	10.776-11.247
46	11.9863	0.4196	11.776-12.196
47	12.9013	0.3763	12.713-13.089
48	13.2702	0.4584	13.041-13.500
49	13.8075	0.5347	13.540-14.075
50	14.2395	0.3775	14.051-14.428

NOTE: Bandpass centers approximate

Sensor/Aircraft Parameters:

Spectral Bands:	50 (digitized to 16-bit resolution)
IFOV:	2.5 mrad
Ground Resolution:	163 feet (50 meter at 65,000 feet)
Swath Width:	22.9 nmi/19.9 nmi (36 km)
Total Scan Angle:	85.92^{o}
Pixels/Scan Line:	716
Scan Rate:	6.25 scans/second
Ground Speed:	400 kts (206 m/second)
Roll Correction:	Plus or minus 3.5 degrees (approx.)

Camera Systems

Various camera systems and films are used for photographic data collection. Film types include high definition color infrared, natural color, and black and white emulsions. Available photographic systems are as follows:

- Wild-Heerbrugg RC-10 metric mapping camera
  - 9 x 9 inch film format
  - 6 inch focal length lens provides area coverage of 16 x 16 nautical miles from 65,000 feet
  - 12 inch focal length lens provides area coverage of 8 x 8 nautical miles from 65,000 feet

- Hycon HR-732 large scale mapping camera
  - 9 x 18 inch film format
  - 24 inch focal length lens provides area coverage of 4 x 8 nautical miles from 65,000 feet

- IRIS II Panoramic camera
  - 4.5 x 34.7 inch film format
  - 24 inch focal length lens
  - 90 degree field of view provides area coverage of 2 x 21.4 nautical miles from 65,000 feet

The U.S. Geological Survey's EROS Data Center at Sioux Falls, South Dakota serves as the archive and product distribution facility for NASA-Ames aircraft acquired photographic and digital imagery. For information regarding photography and digital data (including areas of coverage, products, and product costs) contact EROS Data Center, Customer Services, Sioux Falls, South Dakota 57198 (Telephone: 605-594-6151).

Additional information regarding ER-2 acquired photographic and digital data is available through the Airborne Sensor Facility at Ames Research Center. For specific information regarding flight documentation, sensor parameters, and areas of coverage contact the Airborne Sensor Facility, NASA-Ames Research Center, Mail Stop 240-6, Moffett Field, California 94035-1000 (Telephone: 650-604-6252).

MODIS AIRBORNE SIMULATOR (MAS) FLIGHT LINE INFORMATION FOR 20-MAY-1999 FLIGHT 99-073

	START OF FLIGHT LINE						END OF FLIGHT LINE					
LINE	TIME HH:MM:SS	LAT DEG	LON DEG	SOLAR ZEN	SOLAR AZIM	START HEADING	TIME HH:MM:SS	LAT DEG	LON DEG	SOLAR ZEN	SOLAR AZIM	SCAN LINES
1	13:36:17	31.114	-81.077	51.1	88.5	14.60	13:53:05	32.931	-80.548	47.1	92.6	6276
2	13:53:07	32.935	-80.547	47.1	92.7	16.16	14:10:02	34.793	-79.982	43.3	97.5	6322
3	14:12:06	35.010	-79.912	42.9	98.1	15.27	14:14:36	35.277	-79.828	42.3	98.9	934
4	14:15:21	35.356	-79.803	42.2	99.2	15.03	14:16:35	35.489	-79.761	41.9	99.6	467
5	14:16:39	35.494	-79.760	41.9	99.6	15.05	14:20:10	35.870	-79.640	41.2	100.8	1314
6	14:20:14	35.877	-79.638	41.2	100.8	15.20	14:24:41	36.357	-79.483	40.3	102.3	1661
7	14:36:45	37.699	-79.042	37.9	106.8	16.68	14:41:36	38.232	-78.861	37.0	108.8	1811
8	14:41:38	38.237	-78.859	37.0	108.8	16.21	14:43:11	38.407	-78.801	36.7	109.5	580
9	14:43:14	38.413	-78.799	36.7	109.5	16.39	14:45:00	38.605	-78.733	36.4	110.2	660
10	14:45:03	38.610	-78.736	36.4	110.2	17.61	15:05:32	40.843	-77.936	33.2	119.8	7645
11	15:05:33	40.843	-77.940	33.1	119.8	16.12	15:26:00	43.125	-77.034	30.7	131.1	7633
12	15:27:30	43.238	-77.154	31.1	131.6	279.56	15:31:49	43.311	-77.837	30.9	132.3	1612
13	15:36:29	43.050	-77.739	29.6	133.6	47.04	15:43:00	43.587	-76.996	28.8	138.1	2433
14	15:44:57	43.509	-76.787	28.9	138.4	193.32	15:50:11	42.923	-76.966	28.0	139.6	1954
15	15:50:14	42.914	-76.976	27.9	139.6	194.01	16:17:35	39.854	-77.859	22.8	147.3	10207
16	16:17:36	39.856	-77.856	22.8	147.3	193.71	16:44:55	36.821	-78.663	17.9	158.7	10194
17	16:45:15	36.766	-78.719	17.8	158.6	183.14	16:46:50	36.578	-78.721	17.6	159.6	592
18	16:47:06	36.524	-78.726	17.5	159.8	192.12	16:57:11	35.388	-79.009	15.9	165.7	3764
19	16:57:14	35.383	-79.013	15.9	165.8	191.21	17:19:42	32.818	-79.618	12.9	183.8	8326
20	17:19:44	32.828	-79.615	12.9	183.9	189.50	17:42:15	30.270	-80.184	11.7	209.0	8319

NUMBER OF FILES FOR THIS FLIGHT = 20
TOTAL NUMBER OF SCAN LINES = 82704
DATE THESE FILES WERE PROCESSED = 16-Jun-99
DATE THIS LIST WAS CREATED = 16-Jun-99
GRANULE VERSION = 9

CAMERA FLIGHT LINE DATA
FLIGHT NO. 99-073

Accession # 05343

Sensor # 034

Check Points	Frame Numbers	Time (GMT-hr, min, sec) START	Time (GMT-hr, min, sec) END	Altitude, MSL feet/meters	Cloud Cover/Remarks
A - B	7934-7942	15:28:56	15:32:43	67000/20420	Clear
C - D	9148 - 9156	15:39:51	15:44:34	67000/20420	Clear



FLIGHT 99-073 20 MAY 1999 A/C 809 RC-10 / AVIRIS / MAS50



FLIGHT 99-073 20 MAY 1999 A/C 805 RC-10 / AVIRIS DNC F-19