

## FLIGHT SUMMARY REPORT

**Flight Number:** 98-127  
**Calendar/Julian Date:** 12 September 1998 • 255  
**Sensor Package:** Wild Heerbrugg RC-10  
Airborne Visible and Infrared Imaging  
Spectrometer (AVIRIS)  
**Area(s) Covered:** Sierra Nevada/Rogers Dry Lake, CA

**Investigator(s):** Dozier, UCSB; Green, JPL

**Aircraft #:** 809

### SENSOR DATA

<b>Accession #:</b>	05303	----
<b>Sensor ID #:</b>	076	099
<b>Sensor Type:</b>	RC-10	AVIRIS
<b>Focal Length:</b>	12" 304.89 mm	----
<b>Film Type:</b>	Aerochrome IR SO-134	----
<b>Filtration:</b>	Wratten 12	----
<b>Spectral Band:</b>	510-900 nm	----
<b>f Stop:</b>	11	----
<b>Shutter Speed:</b>	1/300	----
<b># of Frames:</b>	99	----
<b>% Overlap:</b>	60	----
<b>Quality:</b>	Fair	----
<b>Remarks:</b>	Subtract 53 seconds for correct GMT	

## Airborne Science and Applications Program

The Airborne Science Branch at NASA's Dryden Flight Research Center, Edwards, California, operates two ER-2 high altitude aircraft in support of NASA earth science research. The ER-2s are used as readily deployable high altitude sensor platforms to collect remote sensing and in situ data on earth resources, celestial phenomena, atmospheric dynamics, and oceanic processes. Additionally, these aircraft are used for electronic sensor research and development and satellite investigative support.

The ER-2s are flown from various deployment sites in support of scientific research sponsored by NASA and other federal, state, university, and industry investigators. Data are collected from deployment sites in Kansas, Texas, Virginia, Florida, and Alaska. Cooperative international scientific projects have deployed the aircraft to sites in Great Britain, Australia, Chile, Fiji, New Zealand, and Norway.

Photographic and digital imaging sensors are flown aboard the ER-2s in support of research objectives defined by the sponsoring investigators. High resolution mapping cameras and digital multispectral imaging sensors are utilized in a variety of configurations in the ER-2s' four pressurized experiment compartments. The following provides a description of the digital multispectral sensor(s) and camera(s) used for data collection during this flight.

## Airborne Visible and Infrared Imaging Spectrometer

The Airborne Visible and Infrared Imaging Spectrometer (AVIRIS) is the second in the series of imaging spectrometer instruments developed at the Jet Propulsion Laboratory (JPL) for earth remote sensing. This instrument uses scanning optics and four spectrometers to image a 614 pixel swath simultaneously in 224 contiguous spectral bands (0.4-2.4  $\mu\text{m}$ ).

AVIRIS parameters are as follows:

IFOV:	1 mrad
Ground Resolution:	66 feet (20 meters) at 65,000 feet
Total Scan Angle:	30°
Swath Width:	5.7 nmi (10.6 km) at 65,000 feet
Spectral Coverage:	0.41-2.45 $\mu\text{m}$
Pixels/Scan Line:	614
Number of Spectral Bands:	224
Digitization:	10-bits
Data Rate:	17 MBPS

<u>Spectrometer</u>	<u>Wavelength Range</u>	<u>Number of Bands</u>	<u>Sampling Interval</u>
1	0.41 - 0.70 $\mu\text{m}$	31	9.4 nm
2	0.68 - 1.27 $\mu\text{m}$	63	9.4 nm
3	1.25 - 1.86 $\mu\text{m}$	63	9.7 nm
4	1.84 - 2.45 $\mu\text{m}$	63	9.7 nm

All AVIRIS data is decommutated and archived at JPL and not currently available for public distribution. For further information contact Rob Green at Jet Propulsion Laboratory, 4800 Oak Grove Drive, Mail Stop 183-501, Pasadena, California 91109-8099.

## **Camera Systems**

Various camera systems and films are used for photographic data collection. Film types include high definition color infrared, natural color, and black and white emulsions. Available photographic systems are as follows:

- Wild-Heerbrugg RC-10 metric mapping camera
  - 9 x 9 inch film format
  - 6 inch focal length lens provides area coverage of 16 x 16 nautical miles from 65,000 feet
  - 12 inch focal length lens provides area coverage of 8 x 8 nautical miles from 65,000 feet
  
- Hycon HR-732 large scale mapping camera
  - 9 x 18 inch film format
  - 24 inch focal length lens provides area coverage of 4 x 8 nautical miles from 65,000 feet
  
- IRIS II Panoramic camera
  - 4.5 x 34.7 inch film format
  - 24 inch focal length lens
  - 90 degree field of view provides area coverage of 2 x 21.4 nautical miles from 65,000 feet

## **Data Availability**

The U.S. Geological Survey's EROS Data Center at Sioux Falls, South Dakota serves as the archive and product distribution facility for Airborne Science Program aircraft acquired photographic and digital imagery. The photographic archive consists of photography acquired by the program from 1971 to April 1996. For information regarding photography and digital data (including areas of coverage, products, and product costs) contact EROS Data Center, Customer Services, Sioux Falls, South Dakota 57198 (Telephone: 605-594-6151).

As of April 1996 the EROS Data Center no longer receives an archive copy of newly acquired Airborne Science Program photography. Original photography is archived with the Airborne Sensor Facility at Ames Research Center. A user copy of the photography is provided to the principal investigators for each flight. Principal investigators are cited on the first page of their respective flight summary reports. For information regarding photography acquired from April 1996 to the present contact the Airborne Sensor Facility as follows:

## **Flight Documentation and Data Archive Searches**

The following is the web site for flight documentation as published by the Airborne Sensor Facility at NASA Ames Research Center:

<http://asapdata.arc.nasa.gov/er-2fsr.html>

Additional information regarding flight documentation to include data archive searches, data availability, sensor parameters, and areas of coverage may be obtained from the following:

Airborne Sensor Facility  
MS 240-6  
NASA Ames Research Center  
Moffett Field, CA 94035-1000  
Telephone: (650)604-6252 (FAX 4987)

**CAMERA FLIGHT LINE DATA**  
**FLIGHT NO. 98-127**

Accession # 05303

Sensor # 076

Page 1/2

Check Points	Frame Numbers	Time (GMT-hr, min, sec)		Altitude, MSL feet/meters	Cloud Cover/Remarks
		START	END		
A - B	9604-9618	18:15:29	18:22:09	66420/20245	Minor-10% cumulus (frames 9606-9612); oblique (frame 9604)
C - D	9619-9630	18:32:28	18:37:17	66033/20127	Minor-10% cumulus (frames 9620-9622); static discharge (frame 9630)
E - F	9631-9642	18:42:08	18:46:56	66042/20130	Clear; oblique (frames 9631-9632); static discharge (frame 9642)
G - H	9643-9657	18:52:42	18:58:53	66033/20127	Clear; static discharge (frames 9647-9656)
I - J	9658-9664	19:22:16	19:24:40	66114/20152	Clear; static discharge (frame 9664)
I - J	9665-9671	19:33:53	19:36:39	66414/20243	Clear; oblique (frame 9665); static discharge (frame 9671)
I - J	9672-9679	19:45:08	19:47:59	66400/20239	Clear; oblique (frames 9672-9673); static discharge (frame 9679)
I - J	9680-9686	19:56:48	19:59:11	66586/20295	Clear; oblique (frames 9680-9681); static discharge (frame 9686)


**CAMERA FLIGHT LINE DATA**  
**FLIGHT NO. 98-127**

Accession # 05303

Sensor # 076

Page 2/2

Check Points	Frame Numbers	Time (GMT-hr, min, sec)		Altitude, MSL feet/meters	Cloud Cover/Remarks
		START	END		
I - J	9687-9693	20:07:55	20:10:18	66643/20313	Clear; oblique (frames 9687-9688); static discharge (frame 9693)
I - J	9694-9702	20:19:52	20:23:11	66589/20296	Clear; oblique (frame 9694)




FLIGHT 98-127

12 SEPTEMBER 1998

A/C 806

RC-10 / AVIRIS





ONC G-18

RC-10 / AVIRIS

R/C 809

12 SEPTEMBER 1998

FLIGHT 98-127