

FLIGHT SUMMARY REPORT

Flight #: 91-066
Date: 14 March 1991
Sensor Package: Airborne Visible and Infrared Image Spectrometer (AVIRIS)
Wild-Heerbrug RC-10
Area(s) Covered: Utah

Investigator(s): Welch, S.D. School of Mines and Technology

Aircraft #: 706

Flight Request: 91L271

Julian Date: 073

SENSOR DATA

Accession #:	-----	04196
Sensor ID #:	099	036
Sensor Type:	AVIRIS	RC-10
Focal Length:	-----	6" 153.19 mm
Film Type:	-----	High Definition Aerochrome Infrared SO-131
Filtration:	-----	cc.10B
Spectral Band:	-----	510-900 nm
f Stop:	-----	4
Shutter Speed:	-----	1/125
# of Frames:	-----	17
% Overlap:	-----	60
Quality:	-----	Excellent
Remarks:		

Airborne Science and Applications Program

The Airborne Science and Applications Program (ASAP) is supported by three ER-2 high altitude Earth Resources Survey aircraft. These aircraft are operated by the High Altitude Missions Branch at NASA-Ames Research Center, Moffett Field, California. The ER-2s are used as readily deployable high altitude sensor platforms to collect remote sensing and *in situ* data on earth resources, celestial phenomena, atmospheric dynamics, and oceanic processes. Additionally, these aircraft are used for electronic sensor research and development and satellite investigative support.

The ER-2s are flown from various deployment sites in support of scientific research sponsored by NASA and other federal, state, university, and industry investigators. Data are collected from deployment sites in Kansas, Texas, Virginia, Florida, and Alaska. Cooperative international scientific projects have deployed the aircraft to sites in Great Britain, Australia, Chile, and Norway.

Photographic and digital imaging sensors are flown aboard the ER-2s in support of research objectives defined by the sponsoring investigators. High resolution mapping cameras and digital multispectral imaging sensors are utilized in a variety of configurations in the ER-2s' four pressurized experiment compartments. The following provides a description of the digital multispectral sensor used for data collection during this flight.

Airborne Visible and Infrared Imaging Spectrometer

The Airborne Visible and Infrared Imaging Spectrometer (AVIRIS) is the second in the series of imaging spectrometer instruments developed at the Jet Propulsion Laboratory (JPL) for earth remote sensing. This instrument uses scanning optics and four spectrometers to image a 614 pixel swath simultaneously in 224 contiguous spectral bands (0.4-2.4 μm).

AVIRIS parameters are as follows:

IFOV:	1 mrad
Ground Resolution:	66 feet (20 meters) at 65,000 feet
Total Scan Angle:	30°
Swath Width:	5.7 nmi (10.6 km) at 65,000 feet
Spectral Coverage:	0.41-2.45 μm
Pixels/Scan Line:	614
Number of Spectral Bands:	224
Digitization:	10-bits
Data Rate:	17 MBPS

<u>Spectrometer</u>	<u>Wavelength Range</u>	<u>Number of Bands</u>	<u>Sampling Interval</u>
1	0.41 - 0.70 μm	31	9.4 nm
2	0.68 - 1.27 μm	63	9.4 nm
3	1.25 - 1.86 μm	63	9.7 nm
4	1.84 - 2.45 μm	63	9.7 nm


All AVIRIS data is decommutated and archived at JPL and not currently available for public distribution. For further information contact Rob Green at Jet Propulsion Laboratory, 4800 Oak Grove Drive, Mail Stop 183-501, Pasadena, California 91109-8099.

CAMERA FLIGHT LINE DATA
FLIGHT NO. 91-066


Accession # 04196

Sensor # 036

Check Points	Frame Numbers	Time (GMT-hr, min, sec)		Altitude, MSL feet/meters	Cloud Cover/Remarks
		START	END		
A - B	7076-7078	20:10:08	20:11:59	65000/19800	80% alto-cumulus
C - B	7079-7082	20:19:37	20:22:25	"	70-80% alto-cumulus and cumulus
A - B	7083-7084	20:30:58	20:31:54	"	70-80% alto-cumulus and cumulus
B	7085	20:32:50	-----	"	80% alto-cumulus; oblique frame
A - B	7086-7087	20:38:26	20:39:22	"	70-80% alto-cumulus and cumulus
C - B	7088-7090	20:46:52	20:48:52	"	70-80% alto-cumulus and cumulus
B - A	7091-7092	20:50:01	20:50:11	"	80% alto-cumulus and cumulus



FLIGHT 91-066 13 March 1991 A/C 706 AVIRIS / RC-10



FLIGHT 91-086

14 March 1991

A/C 706

RC-10 / AVIRIS

Accession # 04196

ONC 9-19