

FLIGHT SUMMARY REPORT

Flight Number: 95-134
Calendar/Julian Date: 21 July 1995 • 202
Sensor Package: Thematic Mapper Simulator (TMS)
Area(s) Covered: Lake Tahoe/Central Valley, CA

Investigator(s): Functional Sensor

Aircraft #: 706

SENSOR DATA

Accession #: ----
Sensor ID #: 074
Sensor Type: TMS
Focal Length: ----
Film Type: ----
Filtration: ----
Spectral Band: ----
f Stop: ----
Shutter Speed: ----
of Frames: ----
% Overlap: ----
Quality: ----
Remarks:

Airborne Science and Applications Program

The Airborne Science and Applications Program (ASAP) is supported by three ER-2 high altitude Earth Resources Survey aircraft. These aircraft are operated by the High Altitude Missions Branch at NASA-Ames Research Center, Moffett Field, California. The ER-2s are used as readily deployable high altitude sensor platforms to collect remote sensing and *in situ* data on earth resources, celestial phenomena, atmospheric dynamics, and oceanic processes. Additionally, these aircraft are used for electronic sensor research and development and satellite investigative support.

The ER-2s are flown from various deployment sites in support of scientific research sponsored by NASA and other federal, state, university, and industry investigators. Data are collected from deployment sites in Kansas, Texas, Virginia, Florida, and Alaska. Cooperative international scientific projects have deployed the aircraft to sites in Great Britain, Australia, Chile, and Norway.

Photographic and digital imaging sensors are flown aboard the ER-2s in support of research objectives defined by the sponsoring investigators. High resolution mapping cameras and digital multispectral imaging sensors are utilized in a variety of configurations in the ER-2s' four pressurized experiment compartments. The following provides a description of the digital multispectral sensor(s) and camera(s) used for data collection during this flight.

Thematic Mapper Simulator

The Daedalus Thematic Mapper Simulator (TMS) is a multispectral scanner flown aboard the ER-2 aircraft which simulates spatial and spectral characteristics of the seven Landsat-D Thematic Mapper bands. The specific bands are as follows:

<u>Daedalus Channel</u>	<u>TM Band</u>	<u>Wavelength, μm</u>
1	A	0.42 - 0.45
2	1	0.45 - 0.52
3	2	0.52 - 0.60
4	B	0.60 - 0.62
5	3	0.63 - 0.69
6	C	0.69 - 0.75
7	4	0.76 - 0.90
8	D	0.91 - 1.05
9	5	1.55 - 1.75
10	7	2.08 - 2.35
11	6	8.5 - 14.0 low gain
12	6	8.5 - 14.0 high gain

Sensor/aircraft parameters are as follows:

IFOV:	1.25 mrad
Ground Resolution:	81 feet (25 meters) at 65,000 feet
Total Scan Angle:	43°
Swath Width:	8.4 nmi (15.6 km) at 65,000 feet
Pixels/Scan Line:	716
Scan Rate:	12.5 scans/second
Ground Speed:	400 kts (206 m/second)

NOTE: Information on data tape format, logical record format, and scanner calibration data may be obtained from the Aircraft Data Facility, NASA-Ames Research Center, Mail Stop 240-6, Moffett Field, California 94035-1000 (Telephone: 415-604-6252).

TMS SCANNER FLIGHT LINE DATA

FLIGHT NO. 95-134

DALLAS FLIGHT DATA
FLIGHT NUMBER: 95-134

Check Points	Actual		Actual		Scan Speed (FPS)	Total Scanned Scans	Total Interpolated Scans	Total Repeted Scans
	Time Begin	Time End	Scanline Begin	Scanline End				
A-B	20:52: 7.0	21:20: 6.0	65906	66374	12.50	20789	0	0
C-D	21:22:44.0	21:26:50.0	68374	71443	12.50	6070	0	0

